

UTAH-400/DATA

RS-422 Data Router




The UTAH-400/DATA Router is a 64-port RS-422 router designed to switch machine control data in conjunction with the audio/video signal routing layers of a UTAH-400 Digital Routing Switcher System. Each 3ru frame carries a single switch card that serves 64 data ports. A high-speed data bus arrangement is provided to connect up to four frames together to form larger routers with up to 256 ports.

As with all other routers in the UTAH-400 family, dual power supplies are provided as standard equipment. The UTAH-400/DATA router is controlled by the same MX-bus control system as other UTAH-400 frames, allowing it to be added to any SC-4 or SC-400 control system.

UTAH-400/DATA FEATURES

- **COMPACT 3RU PACKAGE**
- **64 RS-422 PORTS PER FRAME**
- **UP TO FOUR FRAMES CAN BE CONNECTED TOGETHER**
- **AUTOMATIC PORT CONFIGURATION**

UTAH-400/DATA Product Information Sheet



The I/O ports on the UTAH-400/DATA Router can be automatically configured by the control system to serve either Controller or Tributary devices. The configuration of any port can be dynamically changed by the control system to allow the switcher to seamlessly follow selections where a device's control port may change between Controller and Tributary modes depending on the operations being carried out by the device.

The UTAH-400/DATA Router's I/O Connections are carried on RJ-45 connectors for easy cabling using standard data networking cables. The connector pin-outs follow the normal pattern for two-pair wiring.

Please see the UCP-Series Product Information Sheet for full details on the wide range of control panels available for the Utah Scientific router control system.

More information on our full line of routing and master control systems is available on the Web at www.utahscientific.com.



New Directions in Digital Switching

4750 Wiley Post Way Suite 150 Salt Lake City, UT 84116
Phone: (801) 575-8801 Fax: (801) 537-3099
EMail: sales@utsci.com www.utahscientific.com